

Material Safety Data Sheet



NFPA



HMIS

Health Hazard	1
Fire Hazard	2
Reactivity	0

Issuing Date **October 31, 2013**

Revision Date **November 22, 2013**

Revision Number **2**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name B3C 2-Cycle with Ethanol Shield
Product Code 10399-F2935
Recommended Use 2-cycle engine oil
Manufactured by: Omni Specialty Packaging
 10399 S. Hwy 1
 Shreveport, LA 71115
 Phone: 1 (318) 524-1100
Emergency Telephone Number CHEMTREC
 1 (800) 424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance Blue **Physical State** Liquid **Odor** Mild

Potential Health Effects

Principal Routes of Exposure Eye contact, Skin contact, Inhalation, Ingestion

Acute Toxicity

Eyes Practically non- irritating to the eye upon direct contact.
Skin Substance minimally irritating upon direct contact.
Inhalation Low hazard at standard temperatures and pressures. Inhalation of oil mist or fumes can cause irritation of the nose, throat and upper respiratory tract
Ingestion Do not ingest. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Other

On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small aspirations.

Chronic Effects Prolonged exposure may cause chronic effects.

Aggravated Medical Conditions Personnel with pre-existing skin disorders should avoid contact with this product.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula	Mixture		
	Chemical Name	CAS-No	Weight %
	Petroleum Distillates, Hydrotreated Heavy Paraffinic	64742-54-7	40-50
	Petroleum Distillates, Solvent Dewaxed heavy Paraffinic	64742-65-0	15-20
	Aliphatic Hydrocarbons	64742-47-8	20-30
	Additive Package	Mixture	20-25
	Dye	Mixture	0-1

4. FIRST AID MEASURES

Eye Contact Flush with large amounts of water for 15 minutes. Get medical attention if eye irritation develops or persists. If material is hot, treat for thermal burns and take victim to the hospital immediately.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes while removing all contaminated clothing and shoes. Get medical attention immediately if skin discoloration occur.

Inhalation This material is not expected to present an inhalation exposure at ambient conditions

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Get immediate medical attention or advice.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable.

Flash Point 177°F

Suitable Extinguishing Media Water Fog. Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable Extinguishing Media Not Available

Hazardous Combustion Products Not Available

Explosion Data

Sensitivity to Mechanical Impact Not sensitive.

Sensitivity to Static Discharge Not sensitive.

Protective Equipment and Precautions for Firefighters Wear positive pressure self-contained breathing apparatus (SCBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal flash point.

NFPA Health Hazard 1 Flammability 2 Stability 0 Physical and Chemical Hazards -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be absorbed on inert material.

Evacuation Procedures
Large Spill Consider initial downwind evacuate for at least 300 meters (1000 feet).
Fire If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Reporting Requirements Spills that enter a water body must be reported immediately to the USEPA's National Response Center at (800)424-8802. Check with your local and state regulators regarding their reporting requirements.

7. HANDLING AND STORAGE

Handling Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30 and OSHA 1910.106 – flammable and combustible liquids.

Storage Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can be dangerous

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Distillates, Hydrotreated Heavy Paraffinic 64742-54-7	5 mg/m3 8 hour(s). Form: Mist	5 mg/m3 8 hour(s). Form: Mist	2,500 mg/m3
Petroleum Distillates, Solvent Dewaxed heavy Paraffinic 64742-65-0	5 mg/m3 8 hour(s). Form: Mist	5 mg/m3 8 hour(s). Form: Mist	2,500 mg/m3
Aliphatic Hydrocarbons 64742-47-8	5 mg/m3 8 hour(s). Form: Mist	5 mg/m3 8 hour(s). Form: Mist	2,500 mg/m3

Engineering Measures Additional area ventilation or local exhaust may be required to maintain air concentrations below recommended limits.

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear goggles. Full face-shield to be worn during emergencies.

Skin and Body Protection As needed to prevent repeated skin contact. Solvent resistant gloves should be used if needed.

Respiratory Protection Not normally needed. During emergencies wear respirator.

Hygiene Measures Remove and wash contaminated clothing before re-use. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Blue	Odor	Mild Petroleum Oder
Physical State	Liquid	pH	N/A
Flash Point	177°F	Autoignition Temperature	N/A
Boiling Point/Range	N/A	Freezing Point	-21°C
Explosion Limits	N/A	Flammability Limits in Air	N/A
Specific Gravity	0.86	Solubility	Negligible
Evaporation Rate	N/A	Vapor Pressure	<0.01
Vapor Density	Not Determined	Density	N/A

10. STABILITY AND REACTIVITY

Stability	Stable under recommended storage conditions.
Incompatible Products	Open Flame and strong oxidizing agents.
Conditions to Avoid	Heat, flames, and sparks.
Hazardous Decomposition Products	Decomposition and combustion products may include smoke, carbon dioxide, carbon monoxide, and toxic fumes.
Hazardous Polymerization	None under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information	Test on similar materials show a low order of acute oral and dermal toxicity.
Acute Oral Effects	Test on similar materials indicates low order of acute toxicity.
Acute Inhalation Effects	Low acute toxicity expected on inhalation.
Skin Effects	Practically non-toxic if absorbed. Other similar highly refined products have not shown skin tumors in mouse skin painting studies.
Eye Irritation	Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on similar products.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum Distillates, Hydrotreated Heavy Paraffinic 64742-54-7	Rat >2000 mg/kg	Rabbit >2000 mg/kg	Rat > 2.18 mg/L 4 hours
Petroleum Distillates, Solvent Dewaxed heavy Paraffinic 64742-65-0	Rat >2000 mg/kg	Rabbit >2000 mg/kg	Rat > 2.18 mg/L 4 hours
Aliphatic Hydrocarbons 64742-47-8	Rat >2000 mg/kg	Rabbit >2000 mg/kg	Rat > 2.18 mg/L 4 hours

Chronic Toxicity

Chronic Toxicity Prolonged exposure may cause chronic effects.

Carcinogenicity

Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

Target Organ Effects Respiratory system, Eyes, Skin, Central nervous system (CNS)

Genotoxicity This product is considered non-mutagenic and has negative potential for tumor development based on results from Modified Ames Assay, with Mutagenic Index of less than 1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity If applied to leaves, this product may kill grasses and small plants by interfering with transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during pelage grooming.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers and waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

	TSCA	DSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Petroleum Distillates, Hydrotreated Heavy Paraffinic 64742-54-7	Present	X	265-157-1	X	X	X	X	X
Petroleum Distillates, Solvent Dewaxed heavy Paraffinic 64742-65-0	Present	X	265-169-7	X	X	X	X	X
Aliphatic Hydrocarbons 64742-47-8	Present	X	265-149-8	X	X	X	X	X

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Florida

No listed ingredients are present

Massachusetts RTK

No listed ingredients are present

Minnesota RTK

No listed ingredients are present

New Jersey RTK

Lists petroleum oil, but this product does not contain hazardous ingredients.

Pennsylvania RTK

Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%.

Illinois DOL TSL

No listed ingredients are present

International Regulations

Mexico – Grade

No information available.

Canada

Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant with Controlled Products Regulation

CONEG Metals

Since cadmium, chromium, lead and mercury are not detectable and it does not exceed 100ppm total in this product, it is compliant with CONEG Metals regulation.

EEC (Europe)

This product is not known to be a dangerous good internationally.

No known R-Phrases or S-Phrases

Hazard Label None

Danger Symbol None

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2B Toxic materials

16. OTHER INFORMATION

Prepared By

Jim Prothro

Issuing Date

October 31, 2013

Revision Date

November 22, 2013

Revision Note

Update product number

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS