



## Safety Data Sheet

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

Date of Revision: 10/02/2024

Revision: 0

### Section 1 - Chemical Product and Company Identification

**Product Name: Ethanol Shield Marine**

**1.2 Synonym:** Blend

**1.3 B3C Fuel Solutions LLC, 108 Daytona Street, Conway, SC 29526, 843-347-0482**

**1.4 Recommended Use:** Fuel system treatment

**1.5 RESTRICTIONS ON USE: THIS STABILIZER IS FOR MARINE GASOLINE ENGINES ONLY**

**1.6 Emergency Response Number: INFOTRAC 1-800-535-5053**

**Local Emergency Telephone Number: 1-352-323-3500**

### Section 2 - Hazards Identification

#### 2.1 GHS HAZARD

##### Hazard Classes

##### Hazard Categories

**Flammable liquid**

**Category 4**

**Eye Irritation**

**Category 2A**

**Skin Irritation**

**Category 2**

**Specific Target Organs single exposure**

**Category 3**

**Acute Toxicity (Oral)**

**Category 4**

**Acute Toxicity (Inhalation)**

**Category 4**

**Acute Toxicity (Dermal)**

**Category 3**

**Mutagenicity**

**Category 1B**

**Carcinogen**

**Category 1B**

**Aspiration Hazard**

**Category 1**

**Aquatic Acute**

**Category 1**

**Aquatic Chronic**

**Category 1**

**2.2 Signal Word: **Danger****

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7



Health

Toxic

Irritant

Aquatic

Hazard Keep away from children

### 2.3 Pictograms:

### 2.4 Hazard Statements

#### PHYSICAL HAZARDS:

H227: Combustible liquid.

#### HEALTH HAZARDS:

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enter the airway.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H340: May cause genetic defects.

H350: May cause cancer.

H372: Causes damage to organs.

#### ENVIRONMENTAL HAZARDS:

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long-lasting effects.

#### PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children.

P201: Obtain special instructions before use.

READ SDS BEFORE USE.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from flames and hot services. No smoking.

P260: Do not breathe vapor and mist.

P264: Wash hands thoroughly after handling

P270: Do not eat, drink, or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, clothing, and eye protection.

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### RESPONSE STATEMENTS:

**P301 +P310+ P331: IF SWALLOWED:**  
Immediately call the National POISON CENTER at **800-222-1222**. DO NOT induce vomiting  
**P303+P361+353: IF ON SKIN or hair.** Rinse skin with water.  
**P304+P340: IF INHALED.** Remove to fresh air and keep comfortable for breathing.  
**PP305+P351+P338: IF IN EYES,** rinse cautiously with water for several minutes. Remove contact lenses, if present, and easy to do so. Continue rinsing.  
**P308+P313:** If exposed or concerned, get medical attention.  
**P312:** the National POISON CENTER at **800-222-1222** if you feel unwell.  
**P313+P332:** If skin irritation occurs, get medical attention.  
**P313 +P337:** If eye irritation persists, get medical attention.  
**H314:** Get medical attention if you feel unwell  
**P330:** Rinse mouth  
**P362+P364:** Take off contaminated clothing and wash it before reuse.  
**P370:** In case of fire, use foam, carbon dioxide, and dry chemical to extinguish a fire.  
**P390:** Collect spillage.

### STORAGE STATEMENTS:

**P403+P405+P235:** Store in a well-ventilated place, store locked up, and keep cool.

### DISPOSAL STATEMENTS:

**P501:** Dispose of content or container following local, regional, national, or international regulations.

**2.5 Hazards not otherwise classified (HNOC) or not covered by GHS:** Ocular eye irritation from vapors inflammation can occur. When splashed in the eye, the liquid may cause burning pain and corneal injury  
**GET MEDICAL ATTENTION. IF IN THE EYES: Rinse cautiously with water for at least 15 minutes.**

### 2.6 Unknown acute toxicity:

8 % of the mixture consists of ingredient(s) of unknown toxicity  
8 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
8 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
8 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
8% of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### Section 3 - Composition / Information on Ingredients

#### 3.1

CAS#	Chemical Names	Synonyms	Percent	Classification
111-76-2	2-Butoxyethanol	Ethylene Glycol Monobutyl Ether	80-100	Acute Tox. 4 H302, Acute Tox. 3 H311 Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox. 4 H332
959934-87-3	Oxirane, 2-ethyl-, homopolymer, 2-aminoethylethyl tridecyl ether, branched	None	7-13	Not classified
128-37-0	2,6-di-tert-butyl-p-cresol	BHT	1-5	Aquatic Chronic 1 H400
64742-82-1	Naphtha, petroleum, hydrodesulfurized heavy	White Spirit	1-5	Asp.Tox.H304, Muta. 1A H340, Carc. 1A H350, STOT RE1 H372
64742-95-6	Naphtha (petroleum), light alkylate	Solvent naphtha (petroleum), light arom	0.1-1	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 H336, Muta. 1B H340, Carc. 1B H350, Aquatic Chronic 2 H411
95-63-6	1,2,4-Trimethylbenzene	Pseudocumene	0.1-1	Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 H335, Acute Tox. 4 H332, Aquatic Chronic 2
108-01-0	2-dimethylaminoethanol	Alkanolamine	0.1-1	Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314. Acute Tox. 4 H332
108-67-8	1,3,5-Trimethylbenzene	Mesitylene	0.1-1	Flam. Liq. 3 H226, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Chronic 2 H411
95-14-7	Benzotriazole	1H- Benzotriazole	0.1-1	Acute Tox. 4 H302, Eye Irrit 2, H319, Aquatic Chronic 2 H411
526-73-8	1,2,3-Trimethylbenzene	Hemimellitene	00.1-1	Flam. Liq. 3 H226, Skin Irrit. 2 H315, Eye Irrit 2, H319

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

1330-20-7	Xylene	Xylol	0.1-1	Flam. Liq. 3 H226, Acute Tox 4 dermal H312, Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox 4 H332
98-82-8	Cumene	2-Phenylpropane	0.1-1	Flam. Liq. 3 H226, Acute Tox 4 dermal H312, Skin Irrit. 2 H315, Eye Irrit 2, H319, Acute Tox 4 H332
91-20-3	*Naphthalene	White Tar	0.1-1	Acute Tox,4 H302, Carc. 2 H351, Aquatic Acute 1 H400, Aquatic Chronic 1 H410

**Note:** \*Naphthalene is a component of Naphtha, petroleum, hydrodesulfurized heavy.

**3.3 Trade Secret Provision and Chemical Concentration Disclosure:** Following OSHA and GHS Regulations, we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and applied to the hazards identified in this Safety Data Sheet.

## Section 4 - First Aid Measures

**4.0 General Advice:** Immediately call The National POISON CENTER at **800-222-1222** or doctor. Provide this SDS to medical personnel for treatment

**4.1 Eye:** Contact with the eyes can cause serious damage. Symptoms may include discomfort, pain, and redness. Severe overexposure can result in swelling of the conjunctiva and tissue damage.

**Eyes:** Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid. Do not apply any medicated agents except on the advice of a physician.

**4.2 Skin:** Contact with skin can cause severe burns.

**Skin:** Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse. Do not apply any medicated agents except on the advice of a physician.

**4.3 Ingestion:** Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting, leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema, and even death.

**Ingestion:** Do not induce vomiting without medical advice. Drink 2-3 large glasses of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. To ensure the airway is open, position with head lower than the body and transport immediately to a medical facility.

**4.4 Inhalation:** Inhaling vapors and aerosols in high concentrations may irritate the respiratory system, cause skin and eye burns, and cause nausea, vomiting, and abdominal pain.

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

**Inhalation:** Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

**4.5 After first aid, get appropriate paramedic or community medical support.** The severity of the outcome following exposure may be more related to the time between exposure and treatment than the amount of exposure. Therefore, there is a need for rapid treatment of any exposure.

**4.6 Note to Physicians:** Treat symptomatically. If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment, we will immediately disclose the specific chemical identity. Call INFOTRAC 800-535-5053 or +1-352-323-3500. We will require a written statement of need and confidentiality agreement following OSHA's Trade Secret Regulations as soon as circumstances permit. We will disclose the specific chemical percentages in non-emergency situations upon written request.

### Section 5 - Fire-Fighting Measures

**5.1 General Fire Hazards:** Use water to cool containers exposed to fire.

**5.2 Hazardous Combustion Products:** Avoid the fumes of burning products.

**5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.

**5.4 Fire Fighting Equipment/Instructions:** Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing and avoid inhaling combustion products.

### Section 6 - Accidental Release Measures

**6.1 Spill /Leak Procedures:** Ventilate area. Wear adequate protective equipment. Spillages of liquid products will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

**6.2 Spills:** Avoid direct contact with the material. Stop the leak if necessary. Move containers from the spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite, or diatomaceous earth and place it in a container for disposal.

### Section 7 - Handling and Storage

**7.1 Handling Precautions:** Avoid ignition sources such as heat, sparks, and open flames. NO SMOKING Take precautionary measures against static discharge. Non-sparking tools should be used. Wear protective gloves, clothing, and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other ignition sources. They may explode and cause injury or death.

**7.2 Storage Requirements:** Store tightly closed containers in their original manufacturer's containers in a cool, dry, well-ventilated area.

**7.3 Chemical Incompatibilities:** Strong oxidizing agents and strong reducing agents.

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### Section 8 - Exposure Controls / Personal Protection

#### 8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
2-Butoxyethanol	20 ppm TWA	25 ppm TWA
Oxirane, 2-ethyl-, homopolymer, 2-aminoethylethyl tridecyl ether, branched	None shown	None shown
2,6-di-tert-butyl-p-cresol	2 mg/m3 TWA	10 mg/m3 TWA
Naphtha, petroleum, hydrodesulfurized heavy	None shown	500 ppm TWA
Benzotriazole	None shown	None shown
Naphthalene	10 ppm TWA	10 ppm TWA
Naphtha (petroleum), light alkylate	None shown	None shown
1,2,4-Trimethylbenzene	10 ppm TWA	25 ppm TWA
2-dimethylaminoethanol	None shown	None shown
1,2,3-Trimethylbenzene	10ppm TWA	25 ppm TWA
Xylene	100 ppm TWA	100 ppm TWA
Cumene	5 ppm TWA	50 ppm TWA

#### 8.2

**ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.**

**OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.**

**NOTE: TWA Means** "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded."

**8.3 Ventilation:** Provide a general or local exhaust ventilation system to maintain airborne concentrations below TLV/PELs. Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

**8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

#### 8.5 Personal protective equipment

##### Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

##### Hand protection

Handle with gloves. Gloves must be inspected before use. Use proper glove removal techniques to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Viton

Splash contact: Viton

Registered trademark of The Chemours Company FC, LLC.

##### Eye protection

Face shield and safety glasses: Use eye protection equipment tested and approved under appropriate government standards, such as NIOSH (US) or EN 166(EU).

##### Skin and body protection

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

Impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### 8.6 Protective Clothing Pictograms



## Section 9 - Physical and Chemical Properties

### 9.1

**Physical state:** Liquid

**Color:** Various

**Odor:** Aromatic Hydrocarbon

**Odor threshold:** Not Available

**Melting point/freezing point:** Not Available

**Boiling point (or initial boiling point or boiling range):** 275-410°F, 135-210°C Estimated

**Flammability:** Combustible

**Lower explosion limit:** Not Available

**Upper explosion limit:** Not Available

**Flashpoint:** 143°F, 62°C c.c. Estimated

**Auto-ignition temperature:** Not Available

**Decomposition temperature:** Not Available

**pH:** Not Available

**Kinematic viscosity:** 2.03cSt @104°F, 40°C

**Solubility:** Insoluble

**Partition coefficient n-octanol/water (log value):** Not Available

**Vapor pressure (includes evaporation rate):** Not Available

**Density:** > 1

**Relative density:** 0.75

Particle characteristics: None

## Section 10 - Stability and Reactivity

**10.1 Stability:** Stable under ordinary conditions of use and storage.

**10.2 Polymerization:** Hazardous polymerization has not been reported.

**10.3 Chemical Incompatibilities:** Strong oxidizing agents and Perchloric acid.

**10.4 Hazardous Decomposition Products:** Peroxides

**10.5 Conditions to Avoid:** Temperatures above 62°C, heat, sparks, open flames, and other ignition sources.

## Section 11- Toxicological Information

### 11.1

Acute Toxicity Estimate for this blend (ATE)



## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

ATE (Oral): 554.9 mg/kg

ATE (Dermal): 524.9mg/kg

ATE (Inhalation vapor/mist): 3.358 mg/l mist

**11.1.1 OECD Guideline Test results** found in the European Chemical Agency Database show that components of this product cause Harmful Oral Toxicity.

**11.1.2 OECD Guideline Test results** found in the European Chemical Agency Database show that no components of this product cause Toxic Dermal Toxicity.

**11.1.3 OECD Guideline Test results** found in the European Chemical Agency Database show that this product's components cause Harmful Inhalation Toxicity.

**11.2 Route of Entry:** Inhalation, Ingestion, Absorption, Skin, and Eye Contact.

**11.3 Aspiration Hazard:** The European Chemical Agency Database shows that components of this product may be fatal if swallowed and enter the airways.

**11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause genetic defects.

**11.5 Skin Corrosion/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that product components cause skin corrosion.

**11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Database show that components of this product cause serious eye damage.

**11.7 Reproductive toxicity:** OECD Guideline Test results in the European Chemical Agency Database show that no components of this product cause damage to fertility or the unborn child.

**11.8 Skin Sensitization** OECD Guideline Test results in the European Chemical Agency Database show that no components of this product cause skin sensitivity.

**11.9 Respiratory Sensitization** OECD Guideline Test results in the European Chemical Agency Database show no components of this product cause respiratory sensitivity.

**11.10 Specific Target Organ Toxicity (Single Exposure):** The European Chemical Agency Database shows that components of this product may damage the central nervous system (CNS).

**11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains chemicals that may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, and central nervous system (CNS).

**11.12 Signs and Symptoms:** Effects due to exposure may include Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, and Seizures. Symptoms may be delayed.

**11.13 Carcinogenicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components cause cancer.

**11.13.1 The National Toxicology Program (NTP):** Cumene and Naphthalene are Carcinogens.

**11.13.2 The International Agency for Research on Cancer (IARC):** Cumene and Naphthalene are Probably carcinogenic to humans,

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

11.13.3 OSHA: None shown

### Section 12 - Ecological Information

#### 12.1

Product Name	Results	Species	Exposure
2-Butoxyethanol	LC50 1490 mg/l	Fish	96 hours
2-Butoxyethanol	LC50 1000 mg/l	Daphnia	48 hours
2-Butoxyethanol	EC50 1840 mg/l	Algae	72 hours
Oxirane, 2-ethyl-, homopolymer, 2-aminoethylethyl tridecyl ether, branched	Harmful to aquatic life with long-lasting effects.		
2,6-di-tert-butyl-p-cresol	LC50 0.199 mg/l	Fish	96 hours
2,6-di-tert-butyl-p-cresol	EC50 0.31 mg/l	Daphnia	48 hours
2,6-di-tert-butyl-p-cresol	EC50 6 mg/l	Algae	72 hours
2,6-di-tert-butyl-p-cresol	EC50 8.98 mg/l	Microtox	30 min.
Naphtha, petroleum, hydrodesulfurized heavy	LC50 30 mg/l	Fish	96 hours
Naphtha, petroleum, hydrodesulfurized heavy	EC50 1000 mg/l	Daphnia	48 hours
Naphtha, petroleum, hydrodesulfurized heavy	IC50 1000 mg/l	Algae	72 hours
Naphtha (petroleum), light alkylate	LC50 2.5 mg/l	Fish	96 hours
Naphtha (petroleum), light alkylate	EC50 1.5 mg/l	Daphnia	48 hours
1,2,4-Trimethylbenzene	LC50 7 mg/l	Fish	96 hours
1,2,4-Trimethylbenzene	EC50 3 mg/l	Daphnia	48 hours
Benzotriazole	LC50 39 mg/l	Fish	96 hours
Benzotriazole	EC50 142 mg/l	Daphnia	48 hours
Benzotriazole	EC50 15.4 mg/l	Algae	72 hours
2-dimethylaminoethanol	LC50 100 mg/l	Fish	96 hours
2-dimethylaminoethanol	EC50 98 mg/l	Daphnia	48 hours
2-dimethylaminoethanol	IC50 35 mg/l	Algae	72 hours
1,2,3-Trimethylbenzene	None shown		
Xylene	LC50 8500 mg/l	Fish	96 hours
Xylene	EC50 13400 mg/l	Daphnia	48 hours
Cumene	LC50 5 mg/l	Fish	96 hours
Cumene	EC50 0.6 mg/l	Daphnia	48 hours
Cumene	IC50 2.6 mg/l	Algae	72 hours
Cumene	EC50 172 mg/l	Microtox	24 hours
Naphthalene	LC50 2 mg/l	Fish	96 hours
Naphthalene	EC50 2 mg/l	Daphnia	48 hours
Naphthalene	IC50 2 mg/l	Algae	72 hours

**Toxicity:** OECD Guideline Test results found in the European Chemical Agency Database show that this product's components are very toxic and can be immediate and long-term toxic to aquatic life.

**12.2 Mobility:** Floats on water.

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

**12.3 Persistence/degradability:** Inconclusive technical data.

**12.4 Bioaccumulation:** Inconclusive technical data.

**12.5 Other adverse effects:** Inconclusive technical data.

### Section 13 - Disposal Considerations

**13.1 Disposal: DO NOT REUSE EMPTY CONTAINER!** The container should be completely emptied before being discarded. Containers with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

### Section 14 - Transport Information

#### 14.1 DOT Transport Information



**IID No.:** UN 2810

**Shipping Name:** Toxic, liquids, organic, n.o.s.( 2-Butoxyethanol)

**Hazard Class:** 6.1


**Packing Group:** III

**Label:** Toxic

**Placard:** Toxic



**Marking:** MARINE POLLUTANT Naphthalene when shipping ground greater than 119 gallons single container or any quantity by water.



Use marking when shipping as a consumer commodity ground in the US

#### 14.42 DOT Transport Limited Quantity

Inner packaging is not over

5.0L (1.3 gallons) net capacity each.

Outer Package not over 30kg (66lbs) each

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

### Section 15 - Regulatory Information

#### 15.1 US Regulations:

**TSCA:** All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**Toxic Release Inventory (TRI):** This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know- Act of 1986 (40 CFR 372):

CAS Number	Chemical Name	Chemical percentage by weight not exceeding
1330-20-7	Xylene,	At demines % limits
98-82-8	Cumene	At demines % limits
95-63-6	1,2,4-trimethylbenzene	At demines % limits
91-20-3	Naphthalene	At demines % limits

This information must be included in all SDSs copied and distributed for this material.

**CERCLA Hazardous Substances and corresponding RQs:** Xylene 100 lbs., Cumene 5000 lbs. Naphthalene 10 lbs.

**SARA Community Right-to-Know Program:** All components of this blend.

**Clean Water Act:** None

**Clean Air Act:** None

**OSHA:** All ingredients are listed in 1910.1200.

#### State Regulations

**California prop. 65:**



**ARNING:** This product can expose you to chemicals, Cumene CAS # 98-82-8 and Naphthalene CAS # 91-20-3, known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**Xylene CAS# 1330-20-7 Considered Reproductive but not listed.**

#### Chemicals on the following State Right to Know Lists:

**Massachusetts:** All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

**New Jersey:** All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

**Pennsylvania:** All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

### Section 16 - Other Information

**16.1 Disclaimer:** The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or failure to adhere to recommended practices. The information provided above

## Ethanol Shield Marine

Conforms to OSHA Hazard Communication Standard 2024 and aligns with the United Nations Globally Harmonized System Revision 7

is furnished on the condition that the person receiving them shall determine the product's suitability for their particular purpose and that they assume the risk of its use.

**16.2 References:** The European Chemical Agency Database and MSDS and SDS of chemicals in this mixture.

**16.3 SJC Compliance Education Inc. (SJC) did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by B3C Fuel Solutions LLC or was reproduced from publicly available regulatory data sources and product SDSs. SJC makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability concerning the use of this information or the substance described in this SDS.**

**16.4 SDS Preparation Date** 10/03/2024

**SDS Previous Issue Date:** None

Prepared by SJC Compliance Education, Inc.

133 N Friendswood Dr.#181

Friendswood TX. 77546

[steve@sjcedu.org](mailto:steve@sjcedu.org)

END OF SAFETY DATA SHEET